Rev. 00 09/2020

# **Technical data sheet NEW NAUTILUS EVO DOUBLE 16**

### 1. DESCRIPTION

Recycled PP formwork for the construction of lightweight bi-directional slabs with flat intrados and large spans.



### 2. TECHNICAL SPECIFICATIONS

Matarial	-	Polipropilene riciclato (PP) 97-99%		
Material	-	Additivi 1-3%		
Percentage of recycled material	%	100		
Colour	-	Nero		
Dimensions *	cm	52x52x H16 (13+3)		
Weight	kg	2.01 (± 10%)		
Lower spacer height	cm	0-5-6-7-8-9-10		
Upper spacer height	cm	0.8		
Formwork volume *	m³/pz	0.033		
Installation time (just plastic component)**	m²/h/operaio	30		
Punching resistance	daN	150		
Fire resistance***	-	REI 180		
Place of production	-	Italy		

<sup>\*</sup> In consideration of the recycled material, the measures should be evaluated with a tolerance of ± 1,5%
\*\* The laying times of the complete slab are subject to considerable variations depending on the amount of reinforcement and the working conditions of the workers.

\*\*\* Value referred to the UNI EN 1365-2 2002 and 1363 2012, carried out with standard sample with dimensions 2.98 x 7.33 m, thickness

<sup>28</sup> cm and subjected to lasts solicitation moment of at least REI 180' with a minimum reinforcement covering of 30mm (EOTA).




Rev. 00 09/2020


# 3. CONCRETE CONSUMPTION CHART

Lower spacer height p	Higher spacer height d	Beam T	Interax i	Incidence of formworks	Concrete consumption flush to the formwork	Formwork volume	Concrete saving flush to the formwork
[cm]	[cm]	[cm]	[cm]	[pz/m²]	[m <sup>3</sup> /m <sup>2</sup> ]	[m³]	[m³/m²]
0-5-6-7-8-9-10	0,8	12	64	2,44	0.079	0,033	0,081
0-5-6-7-8-9-10	0,8	14	66	2,30	0.084	0,033	0,076
0-5-6-7-8-9-10	0,8	16	68	2,16	0.089	0,033	0,071
0-5-6-7-8-9-10	0,8	18	70	2,04	0.093	0,033	0,067
0-5-6-7-8-9-10	0,8	20	72	1,93	0.096	0,033	0,064

<sup>\*</sup> may also be taken into account the concrete saving due to the lower weight of the building

# 4. TECHNICAL DRAWINGS





# 5. PACKAGING AND TRANSPORT

Product code	-	ENNAEDH16XX		
Code composition	-	1 pcs NEW NAUTILUS EVO DOUBLE with spacers included, 2 lateral spacers 10-20cm		
Lower spacer height	cm	0-5-6-7-8-9-10		
Packaging size	cm	110 x 120 x H250		
Type of packaging	-	Stacked and wrapped in plastic film on pallet		
Quantity per pallet	pz	230		
Package gross weight *	kg	475		

<sup>\*</sup> weight may change by (± 10%)